

W





H = Height, W= Width, D = Depth

Н

(€ 🌣



Item number

El-central incl. DEFA PlugIn: 700433 (1xDEFA PlugIn inlet, 1xDEFA PlugIn outlet, 1xSchuko outlet)
Front panel (flush mounting)*: 701101 (White) og 701104 (Mahogany)

* Accessories

Part of

Single pack and part of special boat kits.

Mounting

Read the mounting and user guide carefully. Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger. If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician.

Maintenance

Check the earth-leakage circuit-breaker function within and after the season (marine/boat).

www.defa.com

DEFA El-central 700433

The el-central is moist resistante, but place and fit the el-central on a dry and suitable place on board. Let the connectors point downwards. The el-central can also be flush mounted. Different front panels is available for flush mounting (Accessories).

The el-central got 1 DEFA PlugIn male inlet contact and 2 outlets. 1 PlugIn female contact for DEFA chargers etc. and 1 schuko contact for other electric accessories. All the connectors is placed on one side. The earth wire contact is connected to a "katode protected diode bridge" reducing the corrosion when conneted to shore power.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Technical specifications	
Voltage [VAC]	230
Current [A]	16
IP Rating [IP]	44
H/W/D [mm] (ex. connector)	175x120x90
Weight [kg]	0,92
Acceptance	EN61558-2-4 ISO 13297