






WH 463 HGS
230 V -2000 W



Pesch Marinescheinwerfer
Ortsring 2
D - 21423 Winsen/Luhe

Tel.: +49 4171 5684
E-Mail: sales@seematz.de
<https://www.seematz.de>



WH 463 HGS

230 V -2000 W

Type: WH463HGS2302000

Electrical data: 230V 2000W GY16

Construction features :

Case and all other aluminium parts are made of ALMg3, non magnetic.

Reflector:

high-polished aluminium 99,99%, anodized,
diameter 360mm,focal distance 80mm

Front Pane:

bi-vetral glas, resistant to temperature changes

Sealing:

Seal for front Pane: silicone tube

Seal for plug-in unit: square bar rubber

Lampsocket:

GY16

Electrical Equipment:

Halogen Lamp 2000 W

Burning Position vertical

Technical data lamp:

Power	2000 VA
Voltage	230 V
Current intensity	9.09 A
Luminous flux	52000 lm
Average burning life	400 Hours

Searchlight:

DIN-Range at 1 Lux:	1300 m
IES-Range at ¼ Lux :	3120 m
Beam with at 50 % Imax:	7,5°
Light spot size at target	± 190 m
Power input 230V 2000 VA	
Protective System IP 56	

Turning range:

Horizontal : +/- 165°

Vertical : +/- 30°

Steering Type :

WH (wheelhouse high) Ø 80mm

H = 1000mm (standard size)

E = 500mm (standard size)

Options:

-400 Watt heating rod in searchlight head

-height can be customized (changing of size „H“)

-under deck length can be costumized (changing of size „E“)