




WS 351 LED
24 V - 112 W



Pesch Marinescheinwerfer
Ortsring 2
D - 21423 Winsen/Luhe

Tel.: +49 4171 5684
E-Mail: sales@seematz.de
<https://www.seematz.de>



WS 351 LED

24 V -112 W

Type: WS351LED24112

Electrical data: 24V 112W

Construction features :

Case and all other aluminium parts are made of ALMg3, non magnetic.

Front Pane:

bi-vetral glas, resistant to temperature changes

Sealing:

Seal for front Pane: silicone tube

Seal for plug-in unit: square bar rubber

LED-Type :

Cree XQ-E HI

Technical data lamp:

Power	112 VA
Voltage	24 V
Current intensity	6,5 A
Luminous flux	11100 lm
Average burning life	50000 Hours

Searchlight:

DIN-Range at 1 Lux:	2300 m
IES-Range at ¼ Lux :	4500 m
Beam with at 50 % Imax:	3°
Light spot size at target	±120 m
Power input 24V 112 VA	
Protective System IP 56	

Turning range:

Horizontal :	+/- 165°
Vertical :	+/- 30°

Steering Type :

WS (wheelhouse short) Ø 80mm
E = 500mm (standard size)

Options:

- 400 Watt heating rod in searchlight head
- under deck length can be customized (changing of size „E“)